



9D, Double Dove Great Tower, 438 Pudian Road,
 Shanghai 200122, P. R. China
 Tel: +86-21-50810062, 50811396,
 Fax: +86-21-58818728, 58302954
 cncsh@online.sh.cn <http://www.rokem.com/AtoN.htm>

ML-O350-14 Lantern

Patent No.: ZL 2009 1004 7555.0

ML-O350-14 lantern is a newly developed medium range LED Marine Signal Lantern that use 1, 2, or 4 layers of light source to reach 9~14 nautical miles. ML-O350-14 lantern is suit for medium and large size light buoys at sea and beacons on shore.

Features & Benefits

- Supper bright LED save energy
- High horizontal intensity uniformity
- Line controller select rhythm / No need to open lantern
- Aluminium alloy base with special treatment suits marine environment
- Easy installation and suit equip solar power
- Patent optic design insure high light efficiency
- Computer chip control achieve high reliability
- UV resistant PC for lens
- Pass EMC test

Specifications

- Light source: Supper bright high power LED
- Input voltage: DC12V (10~40V)
- Vertical divergence: 7.5 °(I50%)
- Sun switch: 250±50 lx
- Flash rhythm: 256 rhythms site selectable
- Idling current: ≤4mA
- Temperature: -35°C ~ +55°C
- Protection: IP66
- Dimension: Φ370×420mm,
 Φ370×500mm (2 layers),
 Φ370×660mm (4 layers)
- Installation: 3 and 4-Φ17 on 200mm bolt circle,
 or 3 and 4-Φ17 on 300mm bolt circle
- Weight: 25kg (1 layer, include 5m cable)



Intensity & Range

Color	Layers	Current	Power	Max. intensity	Rang (T=0.74)	1 s intensity	Rang (T=0.74)	0.5s intensity	Rang (T=0.74)
Red	1	3.08A	37W	1050cd	9.4nm	875cd	9.0nm	750cd	8.8nm
	2	7.00A	84W	2200cd	11nm	1833cd	10.6nm	1570cd	10.3nm
	4	13.3A	160W	4100cd	12nm	3416cd	11.9nm	2928cd	11.6nm
Green	1	4.33A	52W	1510cd	10.2nm	1258cd	9.8nm	1078cd	9.5nm
	2	10.0A	120W	3580cd	12nm	2983cd	11.7nm	2557cd	11.3nm
	4	18.2A	218W	6160cd	13.1nm	5133cd	12.7nm	4400cd	12.4nm
White	1	4.59A	55.0W	2600cd	11.3	2166cd	10.9nm	1857cd	10.6nm
	2	10.0A	120W	5500cd	13.0	4583cd	12.5nm	3928cd	12.2nm
	4	20.8A	250W	11000cd	15.0	9166cd	14.1nm	6547cd	13.3nm

- ☆ Please indicate when purchase if you need GPS synchroflash or remote control.
- ☆ Yellow light is not recommended.